



Temperature Screening

Thermographic Camera

Non-contact

Far-distance

Multi-target

Rapid Alarm

V50

Non-contact Fever Screening

Far-distance Large-area Monitoring

Resolution : 80*64

Distance : 1 ~ 2m

Accuracy : ±0.5°C

Capability : 3-4 persons one time

Simultaneously Detect Identification and Body Temperature

15.6-inch HD Screen

Temperature check and identification be clear at a glance

Immediately High Temperature Alarm



Android



LTE



Ethernet



Bluetooth



Temperature Screening



Distance Detection



Camera


V50

Temperature Screening Thermographic Camera


Specification	
OS	Android 6.0 or above
Processor	Quad-Core 1.2GHz
Memory	1GB DDR, 8GB eMMC
Display	5-inch, 720*1280
Temperature Screening	Resolution : 80*64 Distance : 1 ~ 2m Accuracy : ±0.5°C Capability : 3-4 persons one time
Distance sensor	Support distance detection
Camera	Single-lens Camera (RGB), 2MP
SIM Slots (Optional)	1 SIM
Communications	Ethernet/WiFi/Bluetooth LTE (Optional)
Peripheral Ports	1 DC Port, 1 RJ45, 1HDMI, 1 micro USB
Power Supply	12V/2A

Note: Reserve the right to change the parameters without prior notice.


Accessories (Optional)



Wall bracket




Network cable




Tripod


Application



Airport



Border Control



Bank



Office



Public Transportation

Telepower Communication Co.,Ltd.

E-mail: business@telpo.com Skype: [telpo_business](https://www.skype.com/name/telpo_business)

Web: www.telpo.com.cn

Add: Foshan City, Guangdong Province, China

