



Temperature Measuring Terminal

TPS530T



Non-contact Temperature Measurement

Distance : 0 ~10cm
Time : <1s
Range : 32 ~ 42.9 °C
Accuracy : ± 0.3 °C

Rapid Body Temperature Screening

Voice Prompt / High Temperature Alarm

Automatic Information Collection

Contactless Card

Streamline Processes and Reduce Cross-infection

Paperless + Automation +
Cloud Data Management



Android



Telpo Cloud



NFC



Temperature Sensor



Access Control



LTE



GPS

TPS530T

Self-Service Temperature Measuring Terminal

Specification

OS	Android 7.0 or above
Processor	Quad-Core 1.1GHz or above
Memory	1GB DDR, 8GB eMMC 2GB DDR, 16GB eMMC (Optional)
Display	5-inch, 1280*720
Contactless Card Reader	ISO14443 Type A/B, Mifare, ISO18092 compliant EMV Contactless L1, Paywave, Paypass (Optional) Felica(Optional)
Peripheral Ports	Circular Connector:1 RS232+ 1 RS485 Circular Connector:1 DC Charge 1 Micro USB 2 SIM, 2 SAMs, up to 8 SAMs (Optional)
Communications	WCDMA/GPRS/WIFI/Bluetooth LTE (Optional)
GPS (Optional)	Built-in
Temperature Detection	Method : Non-contact Distance : 0 ~10cm Time : <1s Range : 32 ~ 42.9 °C Accuracy : ± 0.3 °C
Built-in 1D/2D Barcode Reader	Soft Decoding, Hard Decoding(Optional)
Audio	Digital Audio Speaker
Dimensions (mm)	285 (L)*168 (W)*95 (H)
Power Supply	DC 9V~40V
MDM (Optional)	Mobile Device Management
Certification	CE

Note: Reserve the right to change the parameters without prior notice.

Accessories



Industry Standard Support



Mounting Bracket

Application



Enterprise



Community



Catereria



Bus



School

Telepower Communication Co.,Ltd.

E-mail: business@telpo.com Skype: [telpo_business](https://www.skype.com/name/telepower)

Web: www.telpo.com.cn

Add: Foshan City, Guangdong Province, China

