

### **Self-Service Kiosk**













Modular Design 80mm Printer



#### **Easy Expansion**

Expandable with additional functional modules based on customer requirements

#### Pogo Pin

Seamlessly integrate peripherals around the display.

- ① Dual-lens face camera
- 2 Array microphone
- 3 Barcode scanner





#### **POS Bracket**

Support for EMV modules including Ingenico Lane3600 and RX7000. \*Support customization of different models of POS brackets




#### **Bank Card Reader**

Support for NFC and chip card reading.

#### **80mm Thermal Printer** with Auto Cutter

Choose between Seiko or Epson solutions to match your operational preferences.



#### **Under-Display NFC**

(Compatible with SoftPOS)



# **K1** Self-Service Kiosk

### **Applications**







Food and Beverage

Healthcare

## **Specifications**

Processor	Octa-Core 2.2GHz	× Face Recognition	Dual-lens Camera
os	Telpo OS (Based on Android 14)	× 1D/2D Barcode Scanner	Support
Memory	4GB RAM, 64GB ROM × 8GB RAM, 128GB ROM	<b>※ Payment</b>	Support various EMV module
Display	21.5", 1080*1920 400NIT Vertical screen	Contactless Card Reader	ISO14443 Type A/B, Mifare
Communications	WiFi 2.4GHz/5GHz(IEEE 802.11a/b/g/n/ac) Bluetooth 5.3	Power Supply	24V/5A
	Ethernet 10/100/1000Mbps  X FDD-LTE/TD-LTE/WCDMAISIM slot, eSIM	× Stand	Floor-stand Desk-stand

**Peripheral Ports** 2 USB-A 2.0, 2 USB-A 3.0, 1 RJ45, 1 Type-C (debug), 1 DC Charge, 3 pogopin

**Audio** Digital Audio Speaker X Array microphone

※ Directional pickup array microphone

Paper width: 80mm,  $\Phi$ 80mm, **Thermal Printer** 

with auto cutter Print speed: 150mm/s

Wall-mounting Bracket

**Shipping Box** Screen: 600\*115\*402mm Dimensions (mm)

Desk bracket: 623(L)\*326(W)\*265(H)

Floor bracket: 872\*490\*328mm

**Environmental** Operating temperature: -5°C ~ 45°C Storage temperature: -25°C ~ 60°C

 $\times$  MDM Mobile Device Management

**XOptional** Datasheet may be revised or amended by product specs.



