Telpo

Temperature Screening

Thermographic Camera

Non-contact | Far-distance | Multi-target | Rapid Alarm

V50+TPS401B

Non-contact Fever Screening

Far-distance Large-area Monitoring

Resolution : 80*64
Distance : 1 ~ 2m
Accuracy : ±0.5°C
Capability : 3-4 persons one time

Simultaneously Detect Identification and Body Temperature

Combined with the display screen, clearly temperature check and identification

Immediately High Temperature Alarm

Android | LTE | Ethernet | Bluetooth | Temperature Screening | Distance Detection | Camera

V50+TPS401B

Temperature Screening Thermographic Camera

Specification

V50 Bullet Camera	
Temperature Module	Resolution : 80*64 Distance : 1m-2m Accuracy : ±0.5°C Capability : 3-4 persons one time
Camera Module	RGB Camera, 2MP, 1920*1080, support HDR
Distance Sensor	Support Distance Detection
Peripheral Ports	2 USB, connecting to control box
Bracket (Optional)	Wall Mount Bracket, Floor Stand
Dimensions (mm)	190(L)*45(W)*90(H)
TPS401B Smart Controller	
OS	Android 7.1
Processor	Dual-Core 1.8GHz(A72) + Quad-Core 1.4GHz(A53)
Memory	4GB DDR, 16GB eMMC, Ext. TF card slot
Communications	Ethernet/WiFi/Bluetooth LTE (Optional)
Peripheral Ports	1xDC Port, 1xRJ45, 1xHDMI, 4xUSB 2.0, 2xUSB 3.0, 1xMicro USB
Power Supply	12V/2A
Accessory (Optional)	1xHDMI Cable
Dimensions (mm)	175(L)*140(W)*30(H)

Note: This products should be used with an electronic display, please additional purchase the display.

Accessories（Optional）

Wall bracket

Network cable

Tripod

Application

Airport

Border Control

Bank

Office

Public Transportation

Telepower Communication Co.,Ltd.

E-mail: business@telpo.com Skype: telpo_business

Web: www.telpo.com.cn

Add: Foshan City, Guangdong Province, China